

EMK 46 Z Built-in magnetic contact



- Conventional built-in magnetic contact
- VdS class B
- ► Head-on or parallel installation
- Conventional perimeter protection


Conventional magnet contacts are used for tear-off surveillance of doors and windows.


Coun- try	Certification	EMK 46 Z
DE	VdS	G 191564, B


Installation/Configuration Notes

Magnetic contact and magnet are mounted in parallel or head-on to each other. Installation can be done optionally with or without plastic sleeves. If no plastic sleeve is used, the built in parts should be fixed in the holes.

Installation in ferromagnetic materials is not permissible.










- 2 Magnet
- 3 Sleeve
- 4 Installation offset




2 Proximity switch part

Connection cable/terminal strip

The supply lines need to be measured electrically before connection.





Parts Included

Туре	Qty.	Components
EMK 46 Z	1	Built in magnetic contact
		incl. flange and sleeves

Technical Specifications

Type of installation	Installation, head-on or parallel
Permitted operating voltage	max. 40 V_
Contact type	1-pin open contact
Permitted contact load	6 VA max. 100 V max. 500 mA
Protective system	IP 67 VdS environmental class IV
Permissible ambient temperature	-25 °C to +70 °C
Case Material Color	ABS White
Dimensions Contact Magnet (W x H x L) Plastic sleeve Connection cable	6 x 30 mm (Ø x L) 6 x 30 mm (Ø x L) 8 x 31 mm (Ø x L) Ø 3.2 mm, 6 m long

Ordering Information

EMK 46 Z Built-in magnetic contact

4998026047

Americas: Bosch Security Systems 130 Perinton Parkway Fairport, New York, 14450, USA Phone: +1 585 223 4060 Fax: +1 800 289 0096 security.sales@us.bosch.com www.boschsecurity.us

Europe, Middle East, Africa: Bosch Security Systems B.V. P.O. Box 80002

P.O. Box 80002 5600 JB Eindhoven, The Netherlands Phone: +31 40 27 83955 Fax: +31 40 27 86668 emea.securitysystems@bosch.com www.boschsecurity.com

Asia-Pacific: Bosch Security Systems Pte Ltd 38C Jalan Pemimpin Singapore 577180 Phone: +65 6319 3450 Fax: +65 6319 3499 apr.securitysystems@bosch.com www.boschsecurity.com

Represented by

@ Bosch Security Systems 2006 | Data subject to change without notice T1512291979 | Cur: en-US, V2, 23 Jan 2006