



ISN-C60 Slim Terminal Connection Contacts



- ▶ Closed loop
- ▶ Install with screws or with super adhesive
- ▶ Breakaway mounting holes for a tight fit
- ▶ Slim terminal connection design
- ▶ Includes deactivated rhodium reed switch
- ▶ Includes screws, super adhesive, mounting holes, and tape cover

The contacts are available in brown or white. Both models have a slim design with breakaway mounting holes for tight-fitting applications. The terminal connection eliminates the need for 15.24 cm or 25.4 cm (6 in. or 10 in.) leads.

Certifications and Approvals

UL and CE

Installation/Configuration Notes

Compatibility Information

All contact models are compatible with control panel models that accept contact inputs.

Parts Included

Quantity Per Package	Component
10	Assemblies (contacts, screws, super adhesive, mounting holes, and tape covers)
10	Magnets

Technical Specifications

Specifications for All Models

Gap Width:	19 mm (0.75 in.)
Contact Dimensions:	6.35 mm x 9.5 mm x 50.8 mm (0.25 in. x 0.375 in. x 2 in.)
Switch Configuration Type:	Single pole single throw (SPST)
Maximum Contact Resistance:	150 $\mu\Omega$ (micro-ohm)
Minimum Breakdown Voltage:	250 VDC
Insulation Resistance:	10 ¹⁰ Ω
Electrostatic Cap:	0.3 PF
Contact Capacity:	10 VAC
Maximum Conductive Current:	1.0 A
Maximum Voltage:	100 V

Package Information

ATTENTION! Each package contains ten assemblies with contacts, screws, super adhesive, mounting holes, tape covers, and ten magnets.

Ordering Information

Brown Slim Terminal Connection Contact	ISN-C60-B
Brown surface mount contact. Package contains ten assemblies with contacts, screws, super adhesive, mounting holes, tape covers, and ten magnets.	

Ordering Information

White Slim Terminal Connection Contact ISN-C60-W

White surface mount contact. **Package contains ten assemblies with contacts, screws, super adhesive, mounting holes, tape covers, and ten magnets.**

Americas:
Bosch Security Systems
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 585 223 4060
Fax: +1 800 289 0096
security.sales@us.bosch.com
www.boschsecurity.us

Europe, Middle East, Africa:
Bosch Security Systems B.V.
P.O. Box 80002
5600 JB Eindhoven, The Netherlands
Phone: +31 40 27 83955
Fax: +31 40 27 86668
emea.securitysystems@bosch.com
www.boschsecurity.com

Asia-Pacific:
Bosch Security Systems Pte Ltd
38C Jalan Pemimpin
Singapore 577180
Phone: +65 6319 3450
Fax: +65 6319 3499
apr.securitysystems@bosch.com
www.boschsecurity.com

Represented by