



ISN-CHS-30 Hidden Screw and Wire Contacts



- ▶ Closed loop
- ▶ Design allows you to conceal screws and wires

The contacts are available in brown or white. Both models are designed so that the screws are concealed and the wires can be brought in from the top, bottom, side, or back. Use for standard applications.

Certifications and Approvals

UL and CE

Installation/Configuration Notes

Compatibility Information

All contact models are compatible with control panel models that accept contact inputs.

Parts Included

Quantity Per Package	Component
10	Contacts
10	Magnets

Technical Specifications

Specifications for All Models

Gap Width:	25 mm (1 in.)
Contact Dimensions:	13 mm x 50.8 mm x 14 mm (0.53 in. x 2 in. x 0.55 in.)
Switch Configuration Type:	Single pole single throw (SPST)
Maximum Contact Resistance:	150 $\mu\Omega$ (micro-ohm)
Minimum Breakdown Voltage:	250 VDC
Insulation Resistance:	$10^{10} \Omega$
Electrostatic Cap:	0.3 PF
Contact Capacity:	10 VAC
Maximum Conductive Current:	1.0 A
Maximum Voltage:	100 V

Package Information

ATTENTION! Each package contains ten contacts and ten magnets.

Ordering Information

Brown Hidden Screw and Wire Contact	ISN-CHS-30B
Brown surface mount contact. Package contains ten contacts and ten magnets.	
White Hidden Screw and Wire Contact	ISN-CHS-30W
White surface mount contact. Package contains ten contacts and ten magnets.	